

M230i-T

Modular and flexible labelling

With the M230i-T4 and M230i-T6 you will get one of the most flexible and safe Print & Apply solutions on the market. Providing a choice of three standard stroke lengths, eight standard non stick pad sizes and left or right hand configuration, the M230i-T4 and M230i-T6 is highly configurable to meet your increasingly demanding and dynamic production environments - both today and in the future.









Performance

- Automatic stroke adaptation to product distances up to 560 mm optimises your throughput.
- Articulated pad allows for label delivery to product panel variances.
- Label Check sensor ensures the label does not get lost, ensuring customer satisfaction for your end user.





Maximum uptime

- 600 m ribbon & label roll capacity within a compact footprint.
- Unique pad design allows for any label variation without changeover.
- Simple preventative maintenance access points.
- Easy to change long life thermal print heads.

Safer by design

- Innovative pinch point protection to prevent incidental contact injuries.
- Autostop feature to prevent damage in the event of an obstruction.
- Air loss detection and protection against system damage.



Modular concept for high flexibility

The modular design of the **M2**30i-T4 and **M2**30i-T6 lets you configure your Print & Apply solution to suit your specific needs.

With three standard stroke lengths, reaching products up to 560 mm from the machine, as well as easily switchable pads ranging from 50×66 mm to 150×210 mm, the solution will give you the flexibility and efficiency you need in your day-to-day operations.



Optional TouchPanel User Interface

For effortless control and status reporting **TouchPanel** is our unique, simplified operator interface that gets the printer into action quickly and simply. No complex menus or parameters, just enter the job and away you go.

- Quick access to favourite menus and settings via large user-friendly icons and customisable home screen.
- Easy prompted input of data into label templates.
- ◆ Speed up changeovers and help eliminate coding selection errors with simplified Message Store and live WYSIWYG preview.

Technical Specification

For labelling on the top, side or bottom, the **M2**30i-T can be configured to suit your specific needs. All M-Series units are equipped with a powerful Printer Control Unit (PCU).

	M2 30i-T4	M2 30i-T6
Print width	108 mm (4'')	162 mm (6'')
Print technology	Thermal Transfer / Direct Thermal	
Resolution	12 dots/mm (300dpi)	
Orientation	Left hand or Right hand	
Label & Ribbon lengths	Up to 600 m	
Typical capacity	60 labels/min	44 labels/min
Distance to product (to center of pad)	Up to 560 mm	
Label sizes (WxL)	25×15* mm - 150×210 mm	
	*55 if Label Check required	
Dimensions (HxWxL)	Min: 625 × 272 × 560 mm Max: 951 × 272 × 671 mm	Min: 625 × 327 × 560 mm Max: 951 × 327 × 671 mm

	PCU
Communication	2xRS232, 1xUSB 2.0, Ethernet
I/Os (configurable)	10 Inputs and 10 Outputs
User interface	Graphical display with 25 languages
Dimensions (HxWxL)	130x280x405 mm









TALK TO AN EXPERT

(S) +91-900 900 6612

enquiry@dominoindia.com www.domino-printing.com



KNOW MORE

