



SAFETY DATA SHEET TIJ-BK150-5 PRINTING INK

According to Regulation (EC) No 1907/2006, Annex II, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name TIJ-BK150-5 PRINTING INK

Product number TIJ-BK150-5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Printing ink.

1.3. Details of the supplier of the safety data sheet

Supplier Domino UK Ltd
Bar Hill
Cambridge
CB23 8TU
Tel: +44 (0) 1954 782551
Fax: +44 (0) 1954 782874
Email: sds@domino-uk.com

1.4. Emergency telephone number

Emergency telephone For emergencies call +44 (0)207 858 0111 (24 Hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Eye Dam. 1 - H318 STOT SE 3 - H336

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H225 Highly flammable liquid and vapour.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/ container in accordance with national regulations.

Contains N-Propanol, Acetone

TIJ-BK150-5 PRINTING INK

Supplementary precautionary statements

P240 Ground and bond container and receiving equipment.
 P241 Use explosion-proof electrical equipment.
 P242 Use non-sparking tools.
 P243 Take action to prevent static discharges.
 P261 Avoid breathing vapour/ spray.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P310 Immediately call a POISON CENTER/ doctor.
 P312 Call a POISON CENTRE/doctor if you feel unwell.
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| | | |
|--|----------------------|--|
| Ethanol | | <70% |
| CAS number: 64-17-5 | EC number: 200-578-6 | REACH registration number: 01-2119457610-43-XXXX |
| Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 | | |
| N-Propanol | | <20% |
| CAS number: 71-23-8 | EC number: 200-746-9 | REACH registration number: 01-2119486761-29-XXXX |
| Classification Flam. Liq. 2 - H225 Eye Dam. 1 - H318 STOT SE 3 - H336 | | |
| tert-ALKYL(C12-C14)AMMONIUMBis[1-[2- & [5-(1,1 & ..., Mixture | | <9% |
| EC No 403-720-7 | | |
| CAS number: 117527-94-3 | EC number: 403-720-7 | REACH registration number: 01-2119848161-43-XXXX |
| Classification Aquatic Chronic 2 - H411 | | |
| Acetone | | <3% |
| CAS number: 67-64-1 | EC number: 200-662-2 | REACH registration number: 01-2119471330-49-XXXX |
| Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336 | | |

TIJ-BK150-5 PRINTING INK

| | | |
|---|----------------------|--|
| 4-Hydroxy-4-methyl-2-pentanone | | <2% |
| CAS number: 123-42-2 | EC number: 204-626-7 | REACH registration number: 01-2119473975-21-XXXX |
| Classification Flam. Liq. 3 - H226 Eye Irrit. 2 - H319 | | |

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|----------------------------|--|
| General information | Get medical attention. Show this Safety Data Sheet to the medical personnel. |
| Inhalation | Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place. |
| Ingestion | IF SWALLOWED: Get medical attention. Rinse mouth thoroughly with water. Do not induce vomiting unless under the direction of medical personnel. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. |
| Skin contact | IF ON SKIN: Rinse immediately with plenty of water. |
| Eye contact | IF IN EYES: Rinse immediately with plenty of water. Get medical attention if irritation persists after washing. |
| Protection of first aiders | First aid personnel should wear appropriate protective equipment during any rescue. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|---------------------|--|
| General information | See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure. |
| Inhalation | A single exposure may cause the following adverse effects: Drowsiness, dizziness, disorientation, vertigo. Headache. Nausea, vomiting. |
| Ingestion | Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. |
| Skin contact | Prolonged contact may cause dryness of the skin. |
| Eye contact | Irritating to eyes. |

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|----------------------|------------------------|
| Notes for the doctor | Treat symptomatically. |
|----------------------|------------------------|

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|--------------------------------|--|
| Suitable extinguishing media | Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |

5.2. Special hazards arising from the substance or mixture

| | |
|-------------------------------|--|
| Specific hazards | Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Containers can burst violently or explode when heated, due to excessive pressure build-up. Take precautionary measures against static discharges. |
| Hazardous combustion products | Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Carbon dioxide (CO ₂). Carbon monoxide (CO). |

5.3. Advice for firefighters

TIJ-BK150-5 PRINTING INK

| | |
|---|--|
| Protective actions during firefighting | Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. |
| Special protective equipment for firefighters | Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|----------------------|--|
| Personal precautions | No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. No smoking, sparks, flames or other sources of ignition near spillage. |
|----------------------|--|

6.2. Environmental precautions

| | |
|---------------------------|--|
| Environmental precautions | Harmful to aquatic life with long lasting effects. Contain spillage with sand, earth or other suitable non-combustible material. Use appropriate containment to avoid environmental contamination. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air). |
|---------------------------|--|

6.3. Methods and material for containment and cleaning up

| | |
|-------------------------|---|
| Methods for cleaning up | Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Collect and dispose of spillage as indicated in Section 13. |
|-------------------------|---|

6.4. Reference to other sections

| | |
|-----------------------------|---|
| Reference to other sections | For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13. |
|-----------------------------|---|

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|--|---|
| Usage precautions | Flammable/combustible materials. Do not handle until all safety precautions have been read and understood. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Use only non-sparking tools. |
| Advice on general occupational hygiene | Wash promptly if skin becomes contaminated. Take off contaminated clothing. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. |

7.2. Conditions for safe storage, including any incompatibilities

| | |
|---------------------|--|
| Storage precautions | Eliminate all sources of ignition. Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep containers upright. Take precautionary measures against static discharges. |
| Storage class | Flammable liquid storage. |

7.3. Specific end use(s)

| | |
|---------------------|---|
| Specific end use(s) | The identified uses for this product are detailed in Section 1.2. |
|---------------------|---|

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

TIJ-BK150-5 PRINTING INK

Occupational exposure limits

Ethanol

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³

N-Propanol

Long-term exposure limit (8-hour TWA): WEL 200 ppm 500 mg/m³

Short-term exposure limit (15-minute): WEL 250 ppm 625 mg/m³

Sk

Acetone

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

4-Hydroxy-4-methyl-2-pentanone

Long-term exposure limit (8-hour TWA): WEL 50 ppm 241 mg/m³

Short-term exposure limit (15-minute): WEL 75 ppm 362 mg/m³

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

Ethanol (CAS: 64-17-5)

| | |
|------|---|
| DNEL | Workers - Inhalation; Long term systemic effects: 950 mg/m ³ Workers - Inhalation; Long term local effects: 1900 mg/m ³ Workers - Dermal; Long term systemic effects: 343 mg/kg/day |
| PNEC | - Fresh water; 0.96 mg/l - Marine water; 0.79 mg/l - Intermittent release; 2.75 mg/l - STP; 580 mg/l - Sediment (Freshwater); 3.6 mg/kg - Sediment (Marinewater); 2.9 - Soil; 0.63 mg/kg |

N-Propanol (CAS: 71-23-8)

| | |
|------|---|
| DNEL | Workers - Inhalation; Long term systemic effects: 268 mg/m ³ Workers - Inhalation; Short term systemic effects: 1723 mg/m ³ Workers - Dermal; Long term systemic effects: 136 mg/kg |
| PNEC | - Fresh water; 10 mg/l - Marine water; 1 mg/l - Intermittent release; 10 mg/l - STP; 96 mg/l - Sediment (Freshwater); 22.8 mg/kg - Sediment (Marinewater); 2.28 mg/kg - Soil; 2.2 mg/kg |

tert-ALKYL(C12-C14)AMMONIUMbis[1-[2- & [5-(1,1 & ..., Mixture EC No 403-720-7 (CAS: 117527-94-3)

| | |
|------|---|
| DNEL | REACH dossier information. Workers - Inhalation; Long term systemic effects: 1.18 mg/m ³ |
| PNEC | REACH dossier information. - Fresh water; 0.1 mg/l - Marine water; 0.01 mg/l - STP; 10 mg/l - Sediment (Freshwater); 0.54 mg/kg - Sediment (Marinewater); 0.054 mg/kg - Soil; 0.049 mg/kg |

Acetone (CAS: 67-64-1)

TIJ-BK150-5 PRINTING INK

DNEL Workers - Dermal; Long term systemic effects: 186 mg/kg/day
Workers - Inhalation; Short term local effects: 2420 mg/m³
Workers - Inhalation; Long term systemic effects: 1210 mg/m³

PNEC - Fresh water; 10.6 mg/l
- Marine water; 1.06 mg/l
- Intermittent release; 21 mg/l
- Sediment (Freshwater); 30.4 mg/kg
- Sediment (Marinewater); 3.04 mg/kg
- Soil; 29.5 mg/kg

4-Hydroxy-4-methyl-2-pentanone (CAS: 123-42-2)

DNEL REACH dossier information.
Workers - Inhalation; Long term systemic effects: 66.4 mg/m³
Workers - Inhalation; Long term local effects: 66.4 mg/m³
Workers - Inhalation; Short term local effects: 240 mg/m³
Workers - Dermal; Long term systemic effects: 9.4 mg/kg/day

PNEC REACH dossier information.
- Fresh water; 2 mg/l
- Marine water; 0.2 mg/l
- Intermittent release; 1 mg/l
- STP; 10 mg/l
- Sediment (Freshwater); 9.06 mg/kg
- Sediment (Marinewater); 0.91 mg/kg
- Soil; 0.63 mg/kg

8.2. Exposure controls

Protective equipment



| | |
|----------------------------------|--|
| Appropriate engineering controls | As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Ensure control measures are regularly inspected and maintained. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. |
| Eye/face protection | Wear tight-fitting, chemical splash goggles or face shield. Personal protective equipment for eye and face protection should comply with European Standard EN166. |
| Hand protection | Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with European Standard EN374. For exposure up to 4 hours, wear gloves made of the following material: Nitrile rubber. The selected gloves should have a breakthrough time of at least 4 hours. For exposure up to 8 hours, wear gloves made of the following material: Butyl rubber. The selected gloves should have a breakthrough time of at least 8 hours. Frequent changes are recommended. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. It should be noted that liquid may penetrate the gloves. |
| Other skin and body protection | Wear anti-static protective clothing if there is a risk of ignition from static electricity. Wear appropriate clothing to prevent skin contamination. |
| Hygiene measures | Provide eyewash station and safety shower. Wash contaminated clothing before reuse. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. |
| Respiratory protection | If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. |
| Environmental exposure controls | Keep container tightly sealed when not in use. |

TIJ-BK150-5 PRINTING INK

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

| | |
|--|--|
| Appearance | Liquid. |
| Colour | Black. |
| Odour | Alcoholic. |
| Odour threshold | Not available. |
| pH | Not available. |
| Melting point | -114°C Information given is applicable to the major ingredient. |
| Initial boiling point and range | ~75°C |
| Flash point | 14°C Closed cup. Information given is applicable to the major ingredient. |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not available. |
| Upper/lower flammability or explosive limits | Lower flammable/explosive limit: 3.3.% Upper flammable/explosive limit: 19% Information given is applicable to the major ingredient. |
| Vapour pressure | 5.81 kPa @ 20°C Information given is applicable to the major ingredient. |
| Vapour density | > 1 |
| Relative density | 0.84 @ 25°C |
| Solubility(ies) | Miscible with water. Soluble in the following materials: Alcohols. |
| Partition coefficient | log Pow: -0.35 Information given is applicable to the major ingredient. |
| Auto-ignition temperature | 365°C Information given is applicable to the major ingredient. |
| Decomposition Temperature | Not available. |
| Viscosity | 2.1 mPa s @ 25°C |
| Explosive properties | Not considered to be explosive. |
| Oxidising properties | Does not meet the criteria for classification as oxidising. |

9.2. Other information

| | |
|---------------------------|---|
| Other information | Not determined. |
| Molecular weight | Not relevant. |
| Volatile organic compound | This product contains a maximum VOC content of <94 %. |

SECTION 10: Stability and reactivity

10.1. Reactivity

| | |
|------------|--|
| Reactivity | See Section 10.3 (Possibility of hazardous reactions) for further information. |
|------------|--|

10.2. Chemical stability

| | |
|-----------|---|
| Stability | Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions. |
|-----------|---|

10.3. Possibility of hazardous reactions

| | |
|------------------------------------|--|
| Possibility of hazardous reactions | The following materials may react strongly with the product: Oxidising agents. |
|------------------------------------|--|

10.4. Conditions to avoid

| | |
|---------------------|--|
| Conditions to avoid | Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented. Do not pressurise, cut, weld, drill, grind or otherwise expose containers to heat or sources of ignition. |
|---------------------|--|

TIJ-BK150-5 PRINTING INK

10.5. Incompatible materials

Materials to avoid Oxidising materials. Acids - oxidising.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Carbon dioxide (CO₂). Carbon monoxide (CO).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Eye Dam. 1 - H318 Causes serious eye damage.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H336 May cause drowsiness or dizziness.

Target organs

Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.

Ingestion

No specific symptoms known.

TIJ-BK150-5 PRINTING INK

| | |
|-------------------|--|
| Skin contact | No specific symptoms known. |
| Eye contact | Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness. |
| Route of exposure | Ingestion Inhalation Skin and/or eye contact |
| Target organs | Central nervous system |

Toxicological information on ingredients.

Ethanol

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 12,400.0

Species Rat

Notes (oral LD₅₀) REACH dossier information.

ATE oral (mg/kg) 12,400.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 17,100.0

Species Rabbit

Notes (dermal LD₅₀) REACH dossier information.

ATE dermal (mg/kg) 17,100.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 125.0

Species Rat

Notes (inhalation LC₅₀) REACH dossier information.

ATE inhalation (vapours mg/l) 125.0

N-Propanol

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 6,500.0

Species Rat

ATE oral (mg/kg) 6,500.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 4,032.0

Species Rabbit

ATE dermal (mg/kg) 4,032.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 33.8

Species Rat

TIJ-BK150-5 PRINTING INK

ATE inhalation (vapours mg/l) 33.8

tert-ALKYL(C12-C14)AMMONIUMBis[1-[2- & [5-(1,1 & ..., Mixture EC No 403-720-7

Acute toxicity - oral

Notes (oral LD₅₀) REACH dossier information. LD₅₀ > 5000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) REACH dossier information. LD₅₀ > 2000 mg/kg, Dermal, Rat

Acetone

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,800.0

Species Rat

ATE oral (mg/kg) 5,800.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 15,700.0

Species Rabbit

ATE dermal (mg/kg) 15,700.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 76.0

Species Rat

ATE inhalation (vapours mg/l) 76.0

4-Hydroxy-4-methyl-2-pentanone

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 3,002.0

Species Rat

ATE oral (mg/kg) 3,002.0

Acute toxicity - dermal

Notes (dermal LD₅₀) REACH dossier information. LD₅₀ > 1875 mg/kg, Dermal, Rat

Acute toxicity - inhalation

Notes (inhalation LC₅₀) REACH dossier information. LC₅₀ >= 7.6 mg/l, Inhalation, Rat

SECTION 12: Ecological Information

Ecotoxicity Harmful to aquatic life with long lasting effects.

12.1. Toxicity

Toxicity Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

Ecological information on ingredients.

Ethanol

Acute aquatic toxicity

TIJ-BK150-5 PRINTING INK

| | |
|--|--|
| Acute toxicity - fish | REACH dossier information. EC ₀ , 200 hours: 3900 mg/l, <i>Oryzias latipes</i> (Red killifish) |
| Acute toxicity - aquatic invertebrates | EC ₅₀ , 24 hours: 20803 mg/l, <i>Daphnia magna</i> |
| Acute toxicity - aquatic plants | NOEC, 7 days: 467 mg/l, Freshwater plants |
| Acute toxicity - microorganisms | IC ₅₀ , 3 hours: >1000 mg/l, Activated sludge |
| Acute toxicity - terrestrial | LC ₅₀ , 48 hours: >1 mg/cm ² , <i>Eisenia Fetida</i> (Earthworm) |
| <u>Chronic aquatic toxicity</u> | |
| Chronic toxicity - fish early life stage | NOEC, 42 hours: 500 mg/l, <i>Brachydanio rerio</i> (Zebra Fish) |
| Chronic toxicity - aquatic invertebrates | LC ₅₀ , 4 days: 12070 mg/l, Marinewater invertebrates |

N-Propanol

Acute aquatic toxicity

| | |
|--|--|
| Acute toxicity - fish | REACH dossier information. LC ₅₀ , 96 hours: 4555 mg/l, <i>Pimephales promelas</i> (Fat-head Minnow) |
| Acute toxicity - aquatic invertebrates | REACH dossier information. LC ₅₀ , 48 hours: 1000 mg/l, Freshwater invertebrates |
| Acute toxicity - aquatic plants | REACH dossier information. NOEC, 48 hours: 1150 mg/l, Algae |
| Acute toxicity - microorganisms | REACH dossier information. IC ₅₀ , 3 hours: >1000 mg/l, Activated sludge |

Chronic aquatic toxicity

| | |
|--|--|
| Chronic toxicity - aquatic invertebrates | REACH dossier information. NOEC, 21 days: >100 mg/l, <i>Daphnia magna</i> |
|--|--|

tert-ALKYL(C12-C14)AMMONIUMBis[1-[2- & [5-(1,1 & ..., Mixture EC No 403-720-7

Acute aquatic toxicity

| | |
|--|--|
| Acute toxicity - fish | REACH dossier information. LC ₅₀ , 24 hours: > 100 mg/l, <i>Brachydanio rerio</i> (Zebra Fish) |
| Acute toxicity - aquatic invertebrates | REACH dossier information. EC ₅₀ , 24 hours: > 1000 mg/l, <i>Daphnia magna</i> |
| Acute toxicity - aquatic plants | REACH dossier information. EC ₅₀ , 72 hours: 0.65 mg/l, <i>Desmodesmus subspicatus</i> |
| Acute toxicity - microorganisms | REACH dossier information. NOEC, 3 hours: > 100 mg/l, Activated sludge |

Acetone

Acute aquatic toxicity

| | |
|--|---|
| Acute toxicity - fish | LC ₅₀ , 96 hours: 5540 mg/l, <i>Oncorhynchus mykiss</i> (Rainbow trout) LC ₅₀ , 96 hours: 11000 mg/l, Marinewater fish |
| Acute toxicity - aquatic invertebrates | EC ₅₀ , 48 hours: 8800 mg/l, Freshwater invertebrates EC ₅₀ , 24 hours: 2100 mg/l, Marinewater invertebrates |
| Acute toxicity - aquatic plants | NOEC, 8 hours: 530 mg/l, Freshwater algae |

TIJ-BK150-5 PRINTING INK

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates NOEC, 28 days: 2212 mg/l, Freshwater invertebrates

4-Hydroxy-4-methyl-2-pentanone

Acute aquatic toxicity

Acute toxicity - fish REACH dossier information.
LC₅₀, 96 hours: > 100 mg/l, *Oryzias latipes* (Red killifish)

Acute toxicity - aquatic invertebrates REACH dossier information.
EC₅₀, 48 hours: > 1000 mg/l, *Daphnia magna*

Acute toxicity - aquatic plants REACH dossier information.
NOEC, 72 hours: 1000 mg/l, *Pseudokirchneriella subcapitata*

Acute toxicity - microorganisms REACH dossier information.
EC₅₀, 3 hours: > 1000 mg/l, Activated sludge

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates REACH dossier information.
NOEC, 21 days: 100 mg/l, *Daphnia magna*

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient log Pow: -0.35 Information given is applicable to the major ingredient.

Ecological information on ingredients.

Ethanol

Partition coefficient log Pow: 0.32

N-Propanol

Partition coefficient log Pow: 0.2

tert-ALKYL(C12-C14)AMMONIUMBis[1-[2- & [5-(1,1 & ...], Mixture EC No 403-720-7

Partition coefficient log Pow: < 3.7

Acetone

Partition coefficient log Pow: -0.24

4-Hydroxy-4-methyl-2-pentanone

Partition coefficient log Pow: -0.09

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

TIJ-BK150-5 PRINTING INK

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|---------------------|---|
| General information | The generation of waste should be minimised or avoided wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. |
| Disposal methods | Dispose of waste product or used containers in accordance with local regulations Only store in correctly labelled containers. |

SECTION 14: Transport information

14.1. UN number

| | |
|------------------|------|
| UN No. (ADR/RID) | 1210 |
| UN No. (IMDG) | 1210 |
| UN No. (ICAO) | 1210 |
| UN No. (ADN) | 1210 |

14.2. UN proper shipping name

| | |
|--------------------------------|--------------|
| Proper shipping name (ADR/RID) | PRINTING INK |
| Proper shipping name (IMDG) | PRINTING INK |
| Proper shipping name (ICAO) | PRINTING INK |
| Proper shipping name (ADN) | PRINTING INK |

14.3. Transport hazard class(es)

| | |
|-----------------------------|----|
| ADR/RID class | 3 |
| ADR/RID classification code | F1 |
| ADR/RID label | 3 |
| IMDG class | 3 |
| ICAO class/division | 3 |
| ADN class | 3 |

Transport labels



14.4. Packing group

| | |
|-----------------------|----|
| ADR/RID packing group | II |
| IMDG packing group | II |
| ADN packing group | II |
| ICAO packing group | II |

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

TIJ-BK150-5 PRINTING INK

| | |
|--|----------|
| EmS | F-E, S-D |
| ADR transport category | 2 |
| Emergency Action Code | •3YE |
| Hazard Identification Number (ADR/RID) | 33 |
| Tunnel restriction code | (D/E) |

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|----------------------|--|
| National regulations | Health and Safety at Work etc. Act 1974 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. EH40/2005 Workplace exposure limits. |
| EU legislation | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). |

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

| | |
|--|--|
| Abbreviations and acronyms used in the safety data sheet | ATE: Acute Toxicity Estimate. CAS: Chemical Abstracts Service. DNEL: Derived No Effect Level. EC ₅₀ : 50% of maximal Effective Concentration. GHS: Globally Harmonized System. IARC: International Agency for Research on Cancer. IATA: International Air Transport Association. Kow: Octanol-water partition coefficient. LC ₅₀ : Lethal Concentration to 50 % of a test population. LD ₅₀ : Lethal Dose to 50% of a test population (Median Lethal Dose). LOAEL: Lowest Observed Adverse Effect Level. NOAEL: No Observed Adverse Effect Level. PBT: Persistent, Bioaccumulative and Toxic substance. PNEC: Predicted No Effect Concentration. REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006. SVHC: Substances of Very High Concern. vPvB: Very Persistent and Very Bioaccumulative. |
| Key literature references and sources for data | Source: European Chemicals Agency, http://echa.europa.eu/ Supplier's information. |
| Revision comments | DUE TO AN UPDATE OF OUR SDS DATABASE THE VERSION NUMBER OF THIS SDS HAS REVERTED TO V1 AND SUPERSEDES PREVIOUS OLDER VERSIONS |
| Revision date | 01/10/2018 |
| Revision | 1 |

TIJ-BK150-5 PRINTING INK

| | |
|---------------------------|--|
| SDS number | 2654 |
| Hazard statements in full | H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.